


- Ductile Iron
- EN124 Class D (400kN)
- AS3996 Class E
- Hinged
- Springbar locking mechanism
- Ventilated and non ventilated options



Reference	Description		Mass (in kg)		Dimensions mm		
	Type	Frame	Total	Cover	Clear Opening	Height	Frame Size
			CDK060EF	Non ventilated			
CDKO60EFX15*	Non ventilated	Round	62	38	606	104	841
CDKO60EF-ST (stormwater)	Non ventilated	Round	62	38	606	104	841
CDKO60EF-SW (sewer)	Non ventilated	Round	62	38	606	104	841
CDKO60EF-SWFISH (stormwater fish)	Non ventilated	Round	62	38	606	104	841
CDK60OEF-WW (waste water)	Non ventilated	Round	62	38	606	104	841
CDKO60FF-WW (waste water)	Ventilated	Round	62	38	606	104	841

* Includes D50 Lock



Ductile iron anti-theft spline
Prevents the cover from being extracted and stolen. It can be installed after the cover is installed

Note: accessories are painted yellow for illustration purposes only.



Anti-intrusion lock :
The lock D50, features a ductile cast iron bar, with high resistance to prevent unauthorised entry.

KORUM Accessories	
CDKO60BF-J	KORUM Blue Elastomer Ring
C38	KORUM Anti Theft Spline
C46	KORUM Opening Key for D50 Lock
C47	KORUM Lock
SGKORUM-IMP	KORUM Safety Grill 1000kg Load Tested
CDKO600SCP	KORUM Stainless Steel Catchpan to suit Ventilated