


PAMREX 600

WITH APPARENT FRAME

- Ductile Iron
- EN124 Class D (400kN)
- AS3996 Class E
- Hinged
- Ventilated and non-ventilated options
- Elastomer ring
- Sealed handling box
- Optional anti-theft cover lock
- Lifting rings integral with the frame
- Frame designed for easy cobble and paving installation, (height= 160 mm) for paved and pedestrian streets



Reference	Description		Mass (in kg)		Dimensions mm		
	Type	Frame	Total	Cover	Clear Opening	Height	Frame Size (OD)
CDPA603F	Non-ventilated	Apparent	132	55	610	160	840 x 840
CDPA604F	Ventilated	Apparent	131	54	610	160	840 x 840

PAMREX 600 Accessories	
SGPAMREX600-IMP	PAMREX 600 Stainless Steel Safety Grill-1000KG Load Tested
C18	PAMREX Opening Key for SCS Lock
C1	PAMREX 600 Galvanised Mudpan
C6	PAMREX 600/700 Penta Lock
C8	PAMREX 600/700 SCS Lock
C17	PAMREX Key for Penta Lock
C45	PAMREX Elastomer Ring
PLUG	PAMREX Hinge Plug

NOTE: The PAMREX grating is interchangeable with any cover of PAMREX 600 series